

Serial No. 09/909,229

Filed: December 30, 2004

Amendments to the Claims

This listing of claims will replace all prior versions, and listings of claims in the application.

LISTING OF CLAIMS:

1. (Currently Amended) A method of transmitting digital information over a synchronous network, the method comprising:
 - a) processing source information at a first rate to generate digital information;
 - b) clocking the digital information without sample rate conversion into the synchronous network at a second rate, the second rate different than the first rate;
 - c) receiving the digital information over the synchronous network; and
 - d) sample rate converting the source information as a function of the first rate and the second rate.
2. (Original) The method of claim 1, wherein the first rate is a different frequency than the second rate.
3. (Currently Amended) The method of claim 1, wherein processing source information a) comprises:
 - counting the first rate to generate a source counter value (CV(m)); and
 - transmitting the source counter value (CV(m)) as part of the digital information.
4. (Currently Amended) The method of claim 1, wherein receiving the digital information c) comprises buffering the digital information.

Serial No. 09/909,229

Filed: December 30, 2004

5. (Currently Amended) The method of claim 1, wherein clocking the digital information b) comprises ~~in Van der Puttening~~ at least two source information words into a network frame for transmittal over the synchronous network.
6. (Currently Amended) The method of claim 1, further comprising e) processing the source information that has been sample rate converted to produce synthesized source information.
7. (Currently Amended) The method of claim 1, further comprising:
- e) transmitting sample rate converted source information over the synchronous network;
 - f) receiving the sample rate converted source information; and
 - g) processing the sample rate converted source information to produce synthesized source information.
8. (Currently Amended) The method of claim 1, wherein sample rate converting d) comprises ignoring a portion of the source information as a function of the first rate and the second rate.
9. (Currently Amended) The method of claim 1, wherein wherein sample rate converting d) comprises sample rate converting the first rate to the second rate.
10. (Currently Amended) The method of claim 1, further comprising:
- e) processing additional source information in synchronism with the second rate to produce additional digital information;

Serial No. 09/909,229

Filed: December 30, 2004

f) clocking the additional digital information into the synchronous network at the second rate;

g) receiving the additional digital information over the synchronous network; and

h) processing the additional digital information absent sample rate conversion to produce synthesized source information.

11. (Currently Amended) A method of processing source information for transmission over a synchronous network, the method comprising:

a) sampling source information at a source sample rate (F_{si});

b) clocking the source information that is sampled at the source sample rate (F_{si}) into a network frame on the synchronous network at a network master clock rate (F_n) that is different from the source sample rate (F_{si});

c) counting the frequency of the source sample rate (F_{si}) during sampling

d) producing a source counter value ($CV(m)$) based on the frequency counted during sampling as a function of c; and

e) clocking the source counter value ($CV(m)$) into the network frame at the network master clock rate (F_n).

12. (Currently Amended) The method of claim 11, further comprising:

f) transmitting the network frame over the synchronous network; and

g) sample rate converting the source information to the network master clock rate (F_n) as a function of the source counter value ($CV(m)$) and the network master clock rate (F_n).

Serial No. 09/909,229

Filed: December 30, 2004

13. (Currently Amended) The method of claim 11, wherein clocking the source information b) comprises ~~in Van der Putter~~ at least two source information words into the network frame.
14. (Currently Amended) The method of claim 11, further comprising ~~g~~ buffering the source information and the source counter value (CV(m)).
15. (Currently Amended) The method of claim 11, wherein sampling source information a) comprises generating the sample rate with a source clock, the source clock operating at a different frequency than the frequency of the network master clock rate (Fn).
16. (Currently Amended) The method of claim 11, wherein clocking the source information b) comprises clocking redundant source information into the network frame as a function of the source sample rate (Fsi) and the network master clock rate (Fn).
17. (Original) The method of claim 11, wherein a ratio of the source sample rate (Fsi) and the network master clock rate (Fn) is less than the number of source information words within the network frame.
18. (Currently Amended) The method of claim 11, wherein a ratio of the source sample rate (Fsi) and the network master clock rate (Fn) is less than or equal to the number of source information words within the network frame.
19. (Original) A method of processing source information transmitted over a synchronous network as digital information, the method comprising:

Serial No. 09/909,229

Filed: December 30, 2004

a) counting the frequency of a network master clock rate (F_n) to produce a network counter value (NCV);

b) extracting a source counter value ($CV(m)$) from digital information transmitted over the synchronous network, the source counter value ($CV(m)$) representing the sample rate of the source information; and

c) sample rate converting the source information as a function of the network counter value (NCV) and the source counter value ($CV(m)$).

20. (Original) The method of claim 19, further comprising d) processing the source information that has been sample rate converted to generate synthesized source information.

21. (Original) The method of claim 19, further comprising:

d) transmitting the sample rate converted source information over the synchronous network to a processing module; and

e) generating synthesized source information with the processing module.

22. (Original) The method of claim 19, wherein c) comprises ignoring a portion of the source information as a function of the source counter value ($CV(m)$) and the network counter value (NCV).

23. (Original) The method of claim 19, wherein c) comprises sample rate converting the source information to the network master clock rate (F_n).

Serial No. 09/909,229

Filed: December 30, 2004

24. (Original) The method of claim 19, wherein c) comprises estimating a ratio of a the network master clock rate (F_n) and a source sample rate (F_{si}) as a function of the network counter value (NCV) and the source counter value ($CV(m)$).

25. (Original) A system for transmitting digital information at various sample rates over a synchronous network, the system comprising:

a source node operable to generate digital information, the digital information comprising source information sampled at a first rate; and

a synchronous network coupled with the source node, the synchronous network operable at a second rate different than the first rate, the digital information clocked into the synchronous network at the second rate absent sample rate conversion.

26. (Original) The system of claim 25, further comprising a sink node coupled with the synchronous network, the sink node operable to process digital information received over the synchronous network to generate synthesized source information.

27. (Original) The system of claim 26, wherein the sink node comprises an output stage coupled with a processing module, the output stage operable to sample rate convert the source information from the first sample rate to the second sample rate and the processing module operable to process the sample rate converted source information and generate synthesized source information.

28. (Original) The system of claim 25, further comprising an output stage coupled with the synchronous network, the output stage operable to sample rate convert the source information

Serial No. 09/909,229

Filed: December 30, 2004

received over the synchronous network to the second rate and input sample rate converted source information into the synchronous network.

29. (Original) The system of claim 28, further comprising a sink node coupled with the synchronous network, the sink node operable to receive the sample rate converted source information over the synchronous network and generate synthesized source information.

30. (Original) The system of claim 25, wherein the source node comprises a source and an input stage, the source operable to provide source information and the input stage operable to generate the digital information as a function of the source information.

31. (Original) The system of claim 25, wherein the digital information is clocked into the synchronous network in a network frame, the network frame comprising at least two source information words.

32. (Original) The system of claim 25, wherein the first rate is a source sample rate (F_{si}) generated by a source clock.

33. (Original) The system of claim 25, wherein the second rate is a network master clock rate (F_n) generated by a network master clock.

34. (Original) The system of claim 25, wherein the digital information further comprises a source counter value ($CV(m)$), the source counter value ($CV(m)$) representative of the first rate.

35. (Original) The system of claim 25, wherein the digital information is also clocked into the synchronous network at the second rate following sample rate conversion to the second rate.